

# The ES **ERGIT** series

# TC



	5400		8400			
<b>Chassis</b>	ACTIO™ – Full chassis with oscillation - Front steering - 4 wheel drive					
<b>Engine type</b>	Direct injection diesel					
<b>N. Cylinders</b>	3		3 Turbo			
<b>Output kW/HP ECE R24</b>	35/48		50/68			
<b>Maximum rpm</b>	2600		2600			
<b>Cooling</b>	Water		Water			
<b>Tank Capacity (litres/gal)</b>	45/12		45/12			
<b>Transmission</b>	Synchronised 32 speed gear box: 16 forward and 16 reverse with synchronised inverter					
<b>PTO</b>	Independent and synchronised at 540/540E rpm with progressive hydraulic engagement					
<b>Hydraulic power lift</b>	3-point hitch Cat. 1					
<b>Capacity (N/Kg-N/lbs)</b>	18620/2000 - 18620/4190					
<b>Brakes</b>	Service disc brakes in oil bath with hydraulic control - Steering brakes					
	Emergency and parking brake: band type on transmission					
<b>Tyres front</b>	7.50-16	7.50-16	8.25x16	250/80x16	7.50-18	250/80x18
<b>Rear</b>	9.5R20	300/70R20	11.2R20	320/70x20	12.4R20	12.4R20
<b>Min. Outer Width (mm/in)</b>	1235/48.6	1290/50.8	1260/49.6	1365/53.7	1330/52.4	1330/52.4
<b>Ground Clearance (mm/in)</b>	265/10.4	265/10.4	280/11	280/11	310/12.2	310/12.2
<b>Weight (Kg/lbs)</b>	1635÷1700/3600÷3750		1650÷1715/3640÷3780			
<b>Dimensions:</b>						
<b>Wheel base (mm/in)</b>	1355/53.3		1355/53.3			
<b>Lenght (mm/in)</b>	3110/122		3110/122			
<b>Height (mm/in)</b>	2170÷2205/85.4÷86.8		2170÷2205/85.4÷86.8			