

The **ERGIT** series

**TRG**



## 9400

<b>Chassis</b>	ACTIO™ – Full chassis with oscillation - Front steering - 4 wheel drive - RGS™ Reversibility				
<b>Engine type</b>	Direct injection diesel				
<b>N. Cylinders</b>	4 Turbo				
<b>Output kW/HP ECE R24</b>	61/83				
<b>Maximum rpm</b>	2600				
<b>Cooling</b>	Water				
<b>Tank Capacity (litres/gal)</b>	60/16				
<b>Transmission</b>	Synchronised 32 speed gear box: 16 forward and 16 reverse with synchronised reverser				
<b>PTO</b>	Indep. with progressive electrohydr. engagement 540/540E rpm and synchronized PTO				
<b>Hydraulic power lift</b>	Position and draft control with 3 point hitch				
<b>Capacity (N/Kg-N/lbs)</b>	22540/2300 - 22540/5070				
<b>Brakes</b>	Service brakes: on 4 wheels disk brakes in oil bath with hydraulic engagement				
	Steering brakes - Emergency and parking: band type on transmission				
<b>Tyres front</b>	11.2 R20	320/70 R20	11L R16	280/70 R18	250/80-18
<b>Rear</b>	12.2 R24	360/70 R24	335/80 R20	360/70 R20	12.4 R20
<b>Min. Outer Width (mm/in)</b>	1415/55.7	1475/58.1	1420/55.9	1545/60.8	1505/59.2
<b>Ground Clearance (mm/in)</b>	410/16.1	410/16.1	355/14	355/14	355/14
<b>Weight with safety bar (Kg/lbs)</b>	<del>2080-2220/4590-4890</del>		2090-2230/4610-4920		
<b>With cab (Kg/lbs)</b>	<del>2220-2360/4890-5200</del>		2230-2370/4920-5220		
<b>Dimensions: wheel base (mm/in)</b>	1620/63.8		1620/63.8		
<b>Lenght (mm/in)</b>	<del>3300-3460/134-136</del>		3340-3500/132-138		
<b>Height: with roll bar (mm/in)</b>	<del>2280-2335/89.8-91.9</del>		2280-2335/89.8-91.9		
<b>With cab (mm/in)</b>	<del>2240-2295/88.2-90.4</del>		2240-2295/88.2-90.4		