

The **30** series



TTR
HST



4400

Chassis	ACTIO™ – Full chassis with oscillation - Front steering - 4 equal wheel drive - RGS™ Reversibility					
Engine type	Direct injection diesel					
N. Cylinders	3					
Output kW/HP ECE R24	25,4/35					
Maximum rpm	3000					
Cooling	Water					
Tank Capacity (litres/gal)	35/9.2					
Transmission	Hydrostatic – Mechanical selector with 3 speed range: low/normal/high Stepless speed variator in both forward and reverse gears from 0 to 27 Km/h					
PTO	Independent PTO with 2 speeds 540 and 1000 rpm					
Hydraulic power lift	3-point hitch Cat. 1					
Capacity (N/Kg-N/lbs)	8330/850 - 8330/1870					
Brakes	Service and parking brakes					
Tyres	6.50-16	7.50-16	28x9.00-15	29x12.00-15	29x12.50-15	7.5L-15
Min. Outer Width (mm/in)	1125/44.3	1165/45.9	1220/48	1365/53.7	1380/54.3	1165/45.9
Ground Clearance (mm/in)	260/10.2	275/10.8	245/9.6	250/9.8	255/10	255/10
Weight with safety bar (Kg/lbs)	1110/2450					
With cab (Kg/lbs)	1340/2950					
Dimensions:						
wheel base (mm/in)	1300/51.2					
Lenght (mm/in)	3110/122					
Height: with roll bar (mm/in)	2010-2040/79.1-80.3					
With cab (mm/in)	2000-2030/79-79.9					